PUBLIC HEALTH SERVICE U.S. FOOD AND DRUG ADMINISTRATION OFFICE OF FOOD SAFETY SHELLFISH AND AQUACULTURE POLICY BRANCH							
U.S. FOOD AND DRUG ADMINISTRATION OFFICE OF FOOD SAFETY							
SHELLFISH LABORATORY EVALUATION CHECKLIST							
LABORATORY:							
ADDRESS:							
TELEPHONE: FAX:							
EMAIL:							
DATE OF EVALUATION: DATE OF REPORT: LAST EVALUATION:							
LABORATORY REPRESENTED BY: TITLE:							
LABORATORY EVALUATION OFFICER: SHELLFISH SPECIALIST:							
REGION:							
OTHER OFFICIALS PRESENT: TITLE:							
Items which do not conform are noted by: Conformity it noted by a " $$ "							
C-Critical K - Key O - Other NA- Not Applicable							
Check the applicable analytical methods:							
Multiple Tube Fermentation Technique for Seawater (APHA)[PART II]							
Multiple Tube Fermentation Technique for Seawater using MA-1 [PART II]							
Membrane Filtration Technique for Seawater using mTEC [PART II]							
Multiple Tube Fermentation Technique for Shellfish Meats (APHA)[PART III]         Standard Plate Count for Shellfish Meats [PART III]							
Elevated Temperature Coliform Plate Method for Shellfish Meats [PART III ]							
Male Specific Coliphage for Soft-shelled Clams and American Oysters [PART III]							

## PART 1 - QUALITY ASSURANCE

CODE	<b>- QUALI</b> REF.				ITEM
K	8,11	1.1	Qua	ality As	ssurance (QA) Plan
			Ì	1.1.1	Written Plan (Check those items which apply.)
					a. Organization of the laboratory.
		Ē	1		b. Staff training requirements.
		Ē	1		c. Standard operating procedures.
		F	1		d. Internal quality control measures for equipment, their calibration,
			_		maintenance, repair, performance, and rejection criteria established.
					e. Laboratory safety.
					f. Internal performance assessment.
					g. External performance assessment.
С	8			1.1.2	QA Plan Implemented.
K	11			1.1.3	The Laboratory participates in a proficiency testing program annually. Specify Program(s)
		1.2	Edu	cation	al/Experience Requirements
С	State's			1.2.1	In state/county laboratories, the supervisor meets the state/county
	Human Resources		_		educational and experience requirements for managing a public health
	Department		_		laboratory.
K	State's Human Resources Department			1.2.2	In state/county laboratories, the analyst(s) meets the state/county educational and experience requirements for processing samples in a public health laboratory.
С	USDA Microbiology & EELAP			1.2.3	In commercial laboratories, the supervisor must have at least a bachelor's degree or equivalent in microbiology, biology, or equivalent discipline with at least two years of laboratory experience.
K	USDA Microbiology & EELAP			1.2.4	In commercial laboratories, the analyst(s) must have at least a high school diploma and shall have at least three months of experience in laboratory sciences.
		1.3	Wo	rk Ar	ea
0	8,11			1.3.1	Adequate for workload and storage.
K	11	Ē	1	1.3.2	Clean, well-lighted.
K	11	F	1	1.3.3	Adequate temperature control.
0	11	F	-	1.3.4	All work surfaces are nonporous, easily cleaned and disinfected.
K	11	Ē	3	1.3.5	Microbiological quality of the air is fewer than 15 colonies for a 15 minute exposure and determined monthly. The results are recorded and records maintained.
		1.4	Lab	orator	y Equipment
0	9	C		1.4.1	To determine the pH of prepared media, the pH meter has a standard accuracy of 0.1 units.
0	14		]	1.4.2	pH electrodes consisting of pH half-cell and reference half-cell or equivalent combination electrode free from (Ag/AgCl) or contains an ion exchange barrier preventing passage of Ag ions into the medium which may affect the accuracy of the pH reading.
K	11			1.4.3	The effect of temperature on the pH is compensated for by an ATC probe or by manual adjustment.
K	8	Ľ		1.4.4	pH meter is calibrated daily or with each use Results are recorded and records maintained.
K	11	C		1.4.5	A minimum of two standard buffer solutions is used to calibrate the pH meter. The first must be near the electrode isopotential point (pH 7). The second near
					the expected sample pH (i.e., pH 4 or pH 10). Standard buffer solutions are used once and discarded.

K       9       1.4.7       Balance provides a sensitivity of at least 0.1 g at weights of use.         K       11,13       1.4.8       Balance calibrations are checked monthly according to manufacturer's specifications using NIST Class S or ASTM Class 1 or 2 weights or equivalent. The accuracy of the balance is verified at the weight range of use. Results are recorded and records maintained.         K       11       1.4.9       Refrigerator temperature(s) are monitored at least once daily on workdays Results are recorded and records maintained.         K       1       1.4.10       Refrigerator temperature of the incubator is maintained at 35 ± 0.5°C.         C       9       1.4.11       The temperature of the incubator(s) are graduated in at least 0 increments.         K       9       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropri placed based on the results of spatial temperature checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         K       9       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the wate					Proposal 19-155
K       11,13       1.4.8       Balance calibrations are checked monthly according to manufacturer's specifications using NIST Class S or ASTM Class 1 or 2 weights or equivalent. The accuracy of the balance is verified at the weight range of use. Results are recorded and records maintained.         K       11       1.4.9       Refrigerator temperature(s) are monitored at least once daily on workdays Results are recorded and records maintained at 05 ± 0.5°C.         C       9       1.4.11       The remperature of the incubator is maintained at 35 ± 0.5°C.         C       11       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers are located on top and bottom shelves or approprial placed based on the results of spatial temperature checks.         C       11       1.4.14       Thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       1.4.16       The acterbath bas adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         C       13       1.4.16       The water of water are appropriately immersed.         C       29       1.4.19       All working thermometers are appropriately immersed.         C       14       1.4.18       Ali incubator/waterbath temperature of waterbath thermometers, or appr			<u> </u>		procedure or through determination of the slope. (Circle the method used.)
Specifications using NIST Class S or ASTM Class 1 or 2 weight range of use. Results are recorded and records maintained.         K       11       I.4.9       Refrigerator temperature(s) are monitored at least once daily on workdays Results are recorded and records maintained.         K       1       I.4.10       Refrigerator temperature is maintained at 0 to 4°C.         C       9       I.4.11       The temperature of the incubator is maintained at 35 ± 0.5°C.         C       11       I.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       I.4.13       Working thermometers used in the maintained at 44.5 ± 0.2°C under all loading conditions.         C       11       I.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       13       I.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         K       9       I.4.17       The lovel of water in the waterbath covers the level of liquid in the incubat tobes.         K       9       I.4.17       The lovel of water in the waterbath covers the level of liquid in the incubat tobes.         K       8, 111       I.4.18       Air incubator/waterbath temperature devices, including Resistance Devices (RTD9) and Platinum Resistance Devices (PTD and Proving thermometers, calibrated decronic devices, including Resistance Devices (PTD and Platinum Resistance Devices (P	K	9		1.4.7	Balance provides a sensitivity of at least 0.1 g at weights of use.
equivalent. The accuracy of the balance is verified at the weight range of use. Results are recorded and records maintained.         K       11       1.4.9       Refrigerator temperature(s) are monitored at least once daily on workdays Results are recorded and records maintained.         K       1       1.4.10       Refrigerator temperature is maintained at 0 to 4°C.         C       9       1.4.11       The temperature of the incubator is maintained at 35 ± 0.5°C.         C       11       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropripaleed based on the results of spatial temperature checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       13       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8, 11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on worklays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are appropriately immersed.         C       29       1.4.20       Working thermometers are appropriately immersed.	K	11,13		1.4.8	
K       11       1.4.9       Refrigerator temperature(s) are monitored at least once daily on workdays Results are recorded and records maintained.         K       1       1.4.10       Refrigerator temperature is maintained at 10 to 4°C.         C       9       1.4.11       The temperature of the incubator is maintained at 35 ± 0.5°C.         C       11       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers used in the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       13       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8.11       1.4.19       Alwring thermometers are either: calibrated mercury-in-glass thermometers, an appropriately alibrated deetronic devices, including Resistance Devices (PTD) and Platinum Resistance Devices (PTD) and appropriately alibrated deetronic devices.         C       29       1.4.20       Working thermometers are either calibrated deetronic devices, including Resistance Devi					
K       11       1.4.9       Refrigerator temperature(s) are monitored at least once daily on workdays, Results are recorded and records maintained.         K       1       1.4.10       Refrigerator temperature is maintained at 0 to 4°C.         C       9       1.4.11       The temperature of the incubator is maintained at 35 ± 0.5°C.         C       11       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropria placed based on the results of spatial temperature checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       13       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8,11       1.4.19       All working thermometers are appropriately immersed.         C       4       1.4.19       All working thermometers are either: calibrated moretry-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated on-maintained.         C       14       1.4.19 </td <td></td> <td></td> <td></td> <td></td> <td></td>					
K       1       Image: Construct State in the second state of the incubator is maintained.         K       1       Image: Construct State St					
K       1       1.4.10       Refrigerator temperature is maintained at 0 to 4°C.         C       9       1.4.11       The temperature of the incubator is maintained at 35 ± 0.5°C.         C       11       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropriplaced based on the results of spatial temperature checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       1.4.16       The thermometers used in the waterbath covers the level of liquid in the incuba tubes.         K       8, 11       1.4.17       The level of water in the waterbath covers the level of liquid on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are appropriately inmersed.         C       29       1.4.20       Working thermometers are appropriately mersed.         C       14.19       All working thermometers are appropriately inmersed.         C       14.19       All working thermometers are appropriately mersed.         C       14.10       1.4.20	K	11		1.4.9	
C       9       1.4.11       The temperature of the incubator is maintained at 35 ± 0.5°C.         C       11       1.4.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropria placed based on the results of spatial temperature checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8, 11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       Working thermometers are either: calibrated mercury-in-glass thermometers, on appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD         C       11       1.4.20       Working thermometers are either: calibrated mercury-in-glass thermometers, on ealibrated by NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5° ETCP). These calibration records are maintained.					
C       11       14.12       Thermometers used in the air incubator(s) are graduated in at least 0 increments.         K       9       14.13       Working thermometers are located on top and bottom shelves or appropria placed based on the results of spatial temperature checks.         C       11       14.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       14.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       14.16       The thermometers used in the waterbath covers the level of liquid in the incuba tubes.         K       8,11       14.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8,11       14.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       14.19       All working thermometers are appropriately immersed.         C       29       14.20       Working thermometers are appropriately immersed.         C       14.19       All working thermometers are appropriately immersed.         C       14.21       Amercury-in-glass thadraft thermometer - allos thermometers, or appropriately calibrated electronic devices, including Resistance or Temperature Devises (RTDs) and Platinum Resistance Devices (PTD to a qualified calibratin taboratory using a primary standard traceable					
K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropriately active checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       9       1.4.16       The thermometers used in the waterbath are graduated in at least 0.1 increments.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8.11       1.4.19       All working thermometers are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are appropriately immersed.         C       29       1.4.20       Working thermometers are cher: calibrated mercury-in-glass thermometers, or appropriately calibrated one-mercury-in-glass thermometers, or appropriately calibrated one-mercury-in-glass thermometers, or appropriately calibrated bectronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD). These calibration records are maintained.         K       9       1.4.21       Amercury-in-glass thermometers, and 44.5°C (45.5° ETCP). These calibration records are maintained.         K       9       1.4.22       Standards thermometers, non-mercury-in-glass thermometers are checked annually devices				1.4.11	The temperature of the incubator is maintained at $35 \pm 0.5$ °C.
K       9       1.4.13       Working thermometers are located on top and bottom shelves or appropria placed based on the results of spatial temperature checks.         C       11       1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8, 11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are either: calibrated mercury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDS) and Platinum Resistance Devices (PTD         C       11       1.4.21       A mercury-in-glass standards thermometer are points 0, 35 and 44.5°C (45.5°         C       11       1.4.21       A mercury-in-glass thermometers, nor-mercury-in-glass thermometers, nor-mercury-in-glass thermometers, nor-mercury-in-glass thermometers, nor-mercury-in-glass thermometers are checked annually for accuracy by ice point determination.         C       29       1.4.23       St	C	11		1.4.12	Thermometers used in the air incubator(s) are graduated in at least $0.1^\circ C$
C       11       I 1.4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8,11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are either: calibrated merury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration taboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5° ETCP). These calibration records are maintained.         K       9       1.4.22       Standards thermometers, non-mercury-in-glass thermometers with an accuracy of ±0.05°C are used as the laboratory using a primary standard traceable NIST or an equivalent working thermometers, and response time of me or low drift electronic resistance thermometers.         K       9       1.4.23       Either mercury					
C       11       I 4.14       Temperature of the waterbath is maintained at 44.5 ± 0.2°C under all loading conditions.         C       9       I 4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       I 4.16       The waterbath has adequate capacity for workload.         K       9       I 4.16       The waterbath has adequate capacity for workload.         K       9       I 4.17       The level of water in the waterbath covers the level of liquid in the incuba trubes.         K       8, 11       I 4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       I 4.19       All working thermometers are appropriately immersed.         C       29       I 4.20       Working thermometers are appropriately immersed.         C       11       I 4.20       Working thermometers are appropriately immersed.         C       11       I 4.20       Working thermometers are appropriately immersed.         C       11       I 4.20       Working thermometers are appropriately immersed.         C       11       I 4.20       Working thermometers are appropriately immersed.         C       11       I 4.20       Working thermometers are checked annually for accuracy. or apupropriately calibrated lealoratory	K	9		1.4.13	
C       9       I.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       I.4.16       The waterbath has adequate capacity for workload.         K       9       I.4.17       The level of water in the waterbath covers the level of liquid in the incubat ubes.         K       8,11       I.4.17       The level of water in the waterbath covers the level of liquid in the incubat ubes.         C       4       I.4.19       All working thermometers are appropriately immersed.         C       4       I.4.19       All working thermometers are appropriately immersed.         C       29       I.4.20       Working thermometers are appropriately immersed.         C       14       I.4.19       All working thermometers are appropriately immersed.         C       29       I.4.20       Working thermometers are appropriately immersed.         C       11       I.4.21       A mercury-in-glass standards thermometer has been calibrated by N1 a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5°C 45.5°C				_	
C       9       □       1.4.15       The thermometers used in the waterbath are graduated in at least 0.1 increments.         C       13       □       1.4.16       The waterbath has adequate capacity for workload.         K       9       □       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8,11       □       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       □       1.4.19       All working thermometers are appropriately immersed.         C       29       □       1.4.20       Working thermometers are either: calibrated mercury-in-glass thermometers, calibrated non-mercury-in-glass thermometers, calibrated pole heronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       □       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5°)         K       9       □       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination.         C       29       □       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers or low drift electronic resistance thermometers with an accuracy (or eacuracy (uncertain	C	11		1.4.14	
C       13       Image: Interments.         C       13       Image: Im	~				
C       13       1.4.16       The waterbath has adequate capacity for workload.         K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incubat tubes.         K       8, 11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are appropriately immersed.         C       29       1.4.20       Working thermometers are either: calibrated mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermonetaries are checked annually for accuracy by ice point determination         C       29       1.4.23       Either mercury-in-glass thermometers are checked annually agai standards thermometer type used.)         K       9       1.4.23       Either mercury-in-glass thermometers, and response time of me or low drift electronic resistance thermometers with an accuracy of ±0.05°C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used.</i> )	C	9		1.4.15	<u> </u>
K       9       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8, 11       1.4.17       The level of water in the waterbath covers the level of liquid in the incuba tubes.         K       8, 11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are appropriately immersed.         C       4       1.4.19       All working thermometers are either: calibrated mercury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD).         C       11       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometaris and end thermination.         C       29       1.4.23       Either mercury-in-glass thermometers, and response time of me or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. (Circle th thermometer type used.)         K       13       1.4.24       Incubator and waterbath working ther	<u> </u>	12		1 4 1 (	
K       8, 11       Image: tubes.       Image: tubes.         K       8, 11       Image: tubes.       Image: tubes.         C       4       Image: tubes.       Image: tubes.         C       4       Image: tubes.       Image: tubes.         C       4       Image: tubes.       Image: tubes.         C       29       Image: tubes.       Image: tubes.         C       11       Image: tubes.       Image: tubes.       Image: tubes.         C       11       Image: tubes.       Image: tubes.       Image: tubes.       Image: tubes.         C       11       Image: tubes.       Image:			┼┝┥		
K       8, 11       1.4.18       Air incubator/waterbath temperatures are taken twice daily on workdays. results are recorded and records maintained.         C       4       1.4.19       All working thermometers are appropriately immersed.         C       29       1.4.20       Working thermometers are either: calibrated mercury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5°)         C       11       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         K       9       1.4.22       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers with an accuracy of ±0.05°C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used.</i> )         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually aga standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         I       1.4.24       Incubator and	ĸ	9		1.4.17	· · ·
C       4       Image: constraint in the image:	V	0 11		1 / 10	
C       4       I.4.19       All working thermometers are appropriately immersed.         C       29       I.4.20       Working thermometers are either: calibrated mercury-in-glass thermometers, or appropriately calibrated leectronic dvices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       I.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       I.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         C       29       I.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermom having the accuracy (uncertainty), tolerance and response time of me or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used</i> .)         K       13       I.4.24       Incubator and waterbath working thermometers are checked annually agai standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       I.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         K       9       I.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other nonocorroding materials.	ĸ	8, 11		1.4.18	
C       29       1.4.20       Working thermometers are either: calibrated mercury-in-glass thermometers, or appropriately calibrated non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         Date of most recent determination       Date of most recent determination.         C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermo having the accuracy (uncertainty), tolerance and response time of me or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used.</i> )         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually agai standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel	C	4		1 4 19	
K       1       1.4.22       Standards thermometers, non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       1.4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5°C ETCP). These calibration records are maintained.         K       9       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         Date of most recent determination			┝╞╡		
appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTD)         C       11       1.4.21         A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermo having the accuracy (uncertainty), tolerance and response time of me or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used.</i> )         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually agai standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Moutl pipetting is not permitted.         O       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriti ingredients and samples.         K       9       1.5.3 <td>C</td> <td>29</td> <td></td> <td>1.4.20</td> <td></td>	C	29		1.4.20	
C       11       Image: Construct of the second se					
C       11       I .4.21       A mercury-in-glass standards thermometer has been calibrated by NI a qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       I .4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         C       29       I .4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. (Circle the thermometer type used.)         K       13       I .4.24       Incubator and waterbath working thermometers are checked annually agai standards thermometer type used.)         K       9       I .4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       11       I .4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         K       9       I .5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       I .5.3       Sample containers are made of glass or some other inert material.         O       9       I .5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo					
A qualified calibration laboratory using a primary standard traceable NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5% ETCP). These calibration records are maintained.         K       9       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermom having the accuracy (uncertainty), tolerance and response time of me or low drift electronic resistance thermometers with an accuracy of < ±0.05°C are used as the laboratory standards thermometer. (Circle the thermometer type used.)	C	11		1.4.21	
K       9       1.4.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used.</i> )         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually agai standards thermometer type used.)         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually agai standards thermometer type used.)         K       13       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         K       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo	-				
K       9       14.22       Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.         C       29       14.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. (Circle the thermometer type used.)         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually again standards thermometer type used.)         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting ingredients and samples.         O       9       1.5.3       Sample containers are made of glass or some other inert material.					NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5°C for
C       29       Image: Laboration and the second and maintained and maintained.         O       11       1.4.24       Incubator and waterbath working thermometers are checked annually again standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         Instrument and Glassware Washing       1.5.1       Uttensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting ingredients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo					ETCP). These calibration records are maintained.
C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometer, non-mercury-in-glass or some other inert material.         O       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting redients and samples.       K       9       1.5.3       Sample containers are made of glass or s	K	9		1.4.22	Standards thermometers are checked annually for accuracy by ice point
C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometer, non-mercury-in-glass is not permitted.         0       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other non-morording materials.       K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting ingredients and samples.       K       9       1.5.4       Dilution bottles and tubes are made of borosil					determination. Results recorded and maintained.
C       29       1.4.23       Either mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometers, non-mercury-in-glass thermometer, non-mercury-in-glass is not permitted.         0       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other non-morording materials.       K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting ingredients and samples.       K       9       1.5.4       Dilution bottles and tubes are made of borosil					
K       13       1.4.24       Incubator and waterbath working thermometers are checked annually agaid standards thermometer type used.)         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually agaid standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         Instrument       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting ingredients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo					Date of most recent determination
or low drift electronic resistance thermometers with an accuracy of $\leq \pm 0.05^{\circ}$ C are used as the laboratory standards thermometer. ( <i>Circle th thermometer type used.</i> )K131.4.24Incubator and waterbath working thermometers are checked annually again standards thermometer at the temperatures at which they are used. Results recorded and records maintained.O111.4.25Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.Istabware and Glassware Washing1.5.1Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.K91.5.2Culture tubes are of a suitable size to accommodate the volume for nutritiving redients and samples.K91.5.3Sample containers are made of glass or some other inert material.O91.5.4Dilution bottles and tubes are made of borosilicate glass or plastic and clooper substance and cl	С	29		1.4.23	Either mercury-in-glass thermometers, non-mercury-in-glass thermometer
±0.05°C are used as the laboratory standards thermometer. (Circle the thermometer type used.)         K       13       1.4.24       Incubator and waterbath working thermometers are checked annually again standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       11       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting redients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clooper silicate glaster silicate glass or plastic and clooper silicate glas					having the accuracy (uncertainty), tolerance and response time of mercury
K       13       Incubator and waterbath working thermometers are checked annually again standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       11       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting ingredients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clooper state and clooper state glass or plastic and cloper state glass or plastic and cloper state gl					
K       13       1.4.24       Incubator and waterbath working thermometers are checked annually again standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting redients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo					
Image: Standards thermometer at the temperatures at which they are used. Results recorded and records maintained.       Image: Standards thermometer at the temperatures at which they are used. Results recorded and records maintained.         Image: Omega: Om				1	
O       11       I.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         O       1.5 Labware and Glassware Washing         O       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutritiring redients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo	K	13		1.4.24	
O       11       1.4.25       Appropriate pipet aids are available and used to inoculate samples. Mouth pipetting is not permitted.         Image: Dot provide the state of the state					
Image: Provide the second state of	0	11		1 4 25	
Image: Instruction of the system of the s	0	11		1.4.25	
O       9       1.5.1       Utensils and containers are clean borosilicate glass, stainless steel or other noncorroding materials.         K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutriting redients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clo			151.1	 N	
K       9       1.5.2       Culture tubes are of a suitable size to accommodate the volume for nutritiving redients and samples.         K       9       1.5.3       Sample containers are made of glass or some other inert material.         O       9       1.5.4       Dilution bottles and tubes are made of borosilicate glass or plastic and clop			1.5 La		
K91.5.2Culture tubes are of a suitable size to accommodate the volume for nutriti ingredients and samples.K91.5.3Sample containers are made of glass or some other inert material.O91.5.4Dilution bottles and tubes are made of borosilicate glass or plastic and clo	0	9		1.5.1	
K91.5.3Sample containers are made of glass or some other inert material.O91.5.4Dilution bottles and tubes are made of borosilicate glass or plastic and clo	TZ I	0		1.5.2	· · · · · · · · · · · · · · · · · · ·
K91.5.3Sample containers are made of glass or some other inert material.O91.5.4Dilution bottles and tubes are made of borosilicate glass or plastic and clo	ĸ	9		1.5.2	
O 9 1.5.4 Dilution bottles and tubes are made of borosilicate glass or plastic and clo	V	0		1.5.2	• •
			<b>⊢ ⊢</b>		
with rubber stoppers, caps or screw caps with nontoxic liners.	0	9		1.5.4	
					with rubber stoppers, caps or screw caps with nontoxic liners.

K	9		1.5.5	Graduations are indelibly marked on dilution bottles and tubes or an acceptable alternative method is used to ensure appropriate volumes.
С	9		1.5.6	Pipettes used to inoculate the sample deliver accurate aliquots, have
Ŭ			1.0.0	unbroken tips and are appropriately graduated. Pipettes larger than 10 mL
				are not used to deliver 1mL aliquots; nor, are pipets larger than 1.1mL
				used to deliver 0.1 mL aliquots.
K	9		1.5.7	Reusable sample containers are capable of being properly washed and sterilized.
K	9		1.5.8	In washing reusable pipettes, a succession of at least three fresh water rinses plus
				a final rinse of distilled/deionized water is used to thoroughly rinse off all the
				detergent.
С	2		1.5.9	An alkaline or acidic detergent is used for washing glassware/labware.
C	11		1.5.10	With each load of labware/glassware washed the contact surface of several
				dry pieces from each load are tested for residual detergent (acid or alkali)
				with aqueous 0.04% bromothymol blue. Results are recorded and records maintained.
		1 ( 64		
		1.6 50		on and Decontamination
K	9		1.6.1	Autoclave(s) are of sufficient size to accommodate the workload.
0	8		1.6.2	Routine autoclave maintenance is performed and the records are maintained.
C	<del>11,</del> 30 <u>, 33</u> ,		1.6.3	The autoclave provides <u>sterilization conditions suitable to the load contents.</u>
	<u>34</u>			Sterilization temperature range may be 119°C - 124°C as determined by the lab's equipment Quality Assurance Verification Testing and recommended
				practices from the media manufacturer. a sterilizing temperature of 121±
				2°C as <u>Sterilization is</u> determined for each load using a <del>calibrated</del> <u>verified</u>
				maximum registering thermometer. As an alternative, an appropriate
				temperature monitoring device is used in place of the maximum registering
			_	thermometer when these are unavailable due to the ban on mercury.
K	11		1.6.4	An autoclave standards thermometer has been calibrated by a qualified
				calibration laboratory using a primary standard traceable to NIST or an $aguivalent$ authority at $121^{\circ}$ C. Calibration at $100^{\circ}$ C the steem point is also
				equivalent authority at 121°C. Calibration at 100°C, the steam point, is also recommended but not required.
K	16		1.6.5	The autoclave standards thermometer is checked every five (5) years for
	10		1.0.2	accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house
				at the steam point (100°C) if it has been previously calibrated at both 100°C and
				121°C. Any change in temperature at the steam point changes the calibrated
				temperature at 121°C by the same magnitude.
U IV	1		1.6.6	Date of most recent determination
K	1		1.6.6	Working autoclave thermometers are checked against the autoclave standards thermometer at 121°C yearly.
				diemionicier at 121 C yearly.
				Date of last check Method
K	11		1.6.7	Spore strips/suspensions appropriate for use in an autoclave media cycle are
				used monthly according to manufacturer's instructions to evaluate the
				effectiveness of the sterilization process. Results are recorded and the records
				maintained.
0	11		1.6.8	Heat sensitive tape is used with each autoclave batch.
K	11, 13		1.6.9	Autoclave sterilization records including length of sterilization, total heat
				exposure time and chamber temperature are maintained.
				Type of record: Autoclave log, computer printout or chart recorder tracings.
K	11		1.6.10	<i>(Circle appropriate type or types.)</i> For dry heat sterilized material, the hot-air sterilizing oven provides heating and
Г			1.0.10	sterilizing temperatures in the range of 160 to 180°C.
K	9		1.6.11	A thermometer capable of determining temperatures accurately in the range of
				160 to $180^{\circ}$ C is used to monitor the operation of the hot-air sterilizing oven
K	13		1.6.12	Records of temperatures and exposure times are maintained for the operation of
1	1		1	

				the hot-air sterilizing oven during use.
K	11		1.6.13	Spore strips/suspensions are used quarterly to evaluate the effectiveness of the
	11			sterilization process in the hot-air oven. Records are maintained.
K	11		1.6.14	Reusable sample containers are sterilized for 60 minutes at 170°C in a hot-air oven or autoclaved for 15 minutes at 121°C.
С	1		1.6.15	The sterility of reusable sample containers is determined for each load sterilized. The results are recorded and the records maintained.
С	1		1.6.16	The sterility of pre-sterilized disposable sample containers is determined for
				each lot received. Results are recorded and the records maintained.
K	9		1.6.17	Reusable pipettes are stored and sterilized in aluminum or stainless steel canisters.
K	9		1.6.18	Reusable pipettes (in canisters) are sterilized in a hot-air oven at 170°C for 2 hours.
С	2		1.6.19	The sterility of reusable pipettes is determined with each load sterilized. Results are recorded and records maintained.
С	2		1.6.20	The sterility of pre-sterilized disposable pipettes is determined with each lot received. Results are recorded and the records maintained.
K	18		1.6.21	Hardwood applicator transfer sticks are properly sterilized.
IX .	10		1.0.21	
				Method of sterilization
С	2		1.6.22	The sterility of the hardwood applicator transfer sticks is checked routinely. Results are recorded and the records maintained.
0	13		1.6.23	Spent broth cultures and agar plates are decontaminated by autoclaving for at least 30 minutes before conventional disposal.
		17M	 edia Pre	paration
K	3, 5	_	1.7.1	Media is commercially dehydrated except in the case of medium A-1 which
K	5, 5		1./.1	must be prepared from the individual components and modified MacConkey agar which may be prepared from its components.
K	11		1.7.2	Media is prepared according to manufacturer's instructions.
0	11		1.7.3	Dehydrated media and media components are properly stored in a cool, clean, dry place.
0	11		1.7.4	Dehydrated media are labeled with date of receipt and date opened.
С	12	⊢Ħ	1.7.5	Caked or expired media or media components are discarded.
C	11		1.7.6	Reagent water is distilled or deionized (circle appropriate choice), tested monthly and exceeds 0.5 megohm-cm resistance (2 megohms-cm in-line) or is less than 2.0 µSiemens/cm conductivity at 25°C. (Circle the appropriate water quality descriptor determined.) Results are recorded and the records maintained.
С	11		1.7.7	Reagent water is analyzed for residual chlorine monthly and is at a non- detectable level (< 0.1 mg/L). Results are recorded and the records maintained.
				Specify method of determination
K	11		1.7.8	Reagent water contains <100 CFU/mL as determined monthly using the heterotrophic plate count method. Results are recorded and the records maintained.
K	11		1.7.9	Media prepared from commercial dehydrated components are sterilized according to the manufacturer's instructions.
K	9		1.7.10	The volume and concentration of media in the tube are suitable for the amount of sample inoculated.
С	11		1.7.11	Total time of exposure of sugar broths to autoclave temperatures does not exceed 45 minutes.
С	1		1.7.12	Media sterility is determined for each load sterilized. Results are recorded and the records maintained.
С	1		1.7.13	
Ľ	1		1./.13	Media productivity is determined using media-appropriate, properly

				Proposal 19-155
				diluted positive and negative control cultures for each lot of dehydrated media received or with each batch of media prepared when the medium is
				made from its individual components.
0	9		1.7.14	Sterile phosphate buffered dilution water is used as the sample diluent.
К	11		1.7.15	The pH of the prepared media is determined after sterilization to ensure that it is consistent with manufacturer's requirements. Results are recorded and records are maintained.
		1.8 Sto	orage of	Prepared Culture Media
K	9		1.8.1	Prepared culture media are stored in a cool, clean, dry space where excessive evaporation and the danger of contamination are minimized.
K	5,11		1.8.2	Brilliant green bile 2% broth and A-1 media are stored in the dark.
K	13		1.8.3	Stored media are labeled with the storage expiration date or the sterilization date.
K	9	17	1.8.4	Storage of prepared culture media at room temperature does not exceed 7 days.
K	2	İ	1.8.5	Storage under refrigeration of prepared culture media with loose fitting closures shall not exceed 1 month.
K	11		1.8.6	Storage under refrigeration of prepared culture media with screw-cap closures does not exceed 3 months.
K	17		1.8.7	All prepared MPN broth media stored under refrigeration must reach room temperature prior to use. Culture tubes containing any type of precipitate or Durham tubes containing air bubbles are discarded.
			ŀ	PART II - SEAWATER SAMPLES
		2.1 Co		and Transportation of Samples
С	11		2.1.1	Sample containers are of a suitable size to contain at least 110 mL of sample
_				and to allow adequate headspace for proper shaking. Seawater samples are collected in clean, sterile, watertight, properly labeled sample containers.
К	1		2.1.2	Samples are identified with collectors name, harvest area, sampling station, time and date of collection.
С	9		2.1.3	Immediately after collection, seawater samples are placed in dry storage (ice chest or equivalent) capable of maintaining a temperature of 0 to 10°C with ice or cold packs for transport to the laboratory. Once received, the samples are placed in the refrigerator unless processed immediately.
0	1		2.1.4	A temperature blank is used to represent the temperature of samples upon receipt at the laboratory. Temperature should be equivalent or less than that of the growing area waters. Results are recorded and maintained.
С	9		2.1.5	Analysis of the sample is initiated as soon as possible after collection. Seawater samples are not tested if they have been held for more than 30 hours from the time of collection.
			2.2	Bacteriological Examination of Seawater by the APHA MPN
С	9		2.2.1	Lactose broth or lauryl tryptose broth is used as the presumptive medium. ( <i>Circle appropriate one.</i> )
С	2		2.2.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained. Positive productivity controlNegative productivity control
С	9		2.2.3	Sample and dilutions of sample are shaken vigorously (25 times in a 12" arc in 7 seconds) before inoculation.
С	9		2.2.4	In a multiple dilution series not less than 3 tubes per dilution are used (5 tubes are recommended).
С	6		2.2.5	In a single dilution series not less than 12 tubes are used (for depuration at least 5 tubes are used).
С	6		2.2.6	In a single dilution series, the volumes analyzed are adequate to meet the

				Proposal 19-135
				Sample volume inoculated
				Range of MPN
				Strength of media used
K	9		2.2.7	Inoculated tubes are incubated in air at $35 \pm 0.5^{\circ}$ C.
С	2		2.2.8	Appropriately diluted process control cultures accompany the samples
				throughout both the presumptive and confirmed phases of incubation. Results are recorded and the records maintained.
				Positive process control Negative process control
K	9		2.2.9	Inoculated tubes are read after $24 \pm 2$ hours and $48 \pm 3$ hours of incubation and transferred at both time interval if positive for growth (the presence of turbidity) and gas or effervescence in the culture tube. These tubes are considered presumptive positive requiring further confirmatory testing.
				2.3 Confirmed Test for Seawater by APHA MPN
С	9		2.3.1	Brilliant green bile 2% broth (BGB) is used as the confirmatory medium for total coliforms.
С	9	i 🗖	2.3.2	EC medium is used as the confirmatory medium for fecal coliforms.
С	2		2.3.3	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained.
				Positive productivity control Negative productivity control
K	9, 11		2.3.4	Transfers are made to BGB/EC by either sterile loop or sterile hardwood transfer stick from positive presumptive tubes incubated for 24 and 48 hours as appropriate. ( <i>Circle the method of transfer.</i> )
С	9		2.3.5	BGB tubes are incubated at $35 \pm 0.5^{\circ}$ C.
K	9	H	2.3.6	BGB tubes are read after $48 \pm 3$ hours of incubation.
С	9		2.3.7	EC tubes are incubated in a circulating waterbath maintained at $44.5 \pm 0.2$ °C.
С	9	Ϊ Π	2.3.8	EC tubes are read after $24 \pm 2$ hours of incubation.
С	9		2.3.9	The presence of turbidity and any amount of gas or effervescence in the culture tube constitutes a positive test.
		2.4 Co	mputat	ion of Results – APHA MPN
K	9		2.4.1	Results of multiple dilution tests are read from tables in <i>Recommended</i> <i>Procedures for the Examination of Sea Water and Shellfish</i> , Fourth Edition.
K	7		2.4.2	Results from single dilution series are calculated from Hoskins' equation or interpolated from Figure 1, Public Health Report 1621 entitled "Most Probable Numbers for Evaluation of Coli aerogenes Tests by Fermentation Tube Method".
С	7,9		2.4.3	Results are reported as MPN/100 mL of sample.
			2.5 I	Bacteriological Examination of Seawater by the MA-1 Method
С	5		2.5.1	A-1 medium complete is used in the analysis.
С	2, 31		2.5.2	A-1 medium without salicin is used in the analysis. Comparability testing supports use of A-1 medium without salicin. Study records are available.
С	5		2.5.3	A-1 medium sterilized for 10 minutes at 121°C.
С	2		2.5.4	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained. Positive productivity controlNegative productivity control
С	9		2.5.5	Sample and dilutions of sample are shaken vigorously (25 times in a 12" arc in 7 seconds) before inoculation.
С	9		2.5.6	In a multiple dilution series not less than 3 tubes per dilution are used (5
	Section I	V Guide	ance Doc	uments – Chapter II, Growing Areas NSSP Lab Evaluation Checklist

				tubes are recommended).
С	6		2.5.7	In a single dilution series at least 12 tubes are used.
		┼┝┥		6
C	6		2.5.8	In a single dilution series, the volumes analyzed are adequate to meet the needs of routine monitoring. Sample volume inoculated Range of MPN Strength of media used
С	2		2.5.9	Appropriately diluted process control cultures accompany the samples throughout both resuscitation and waterbath incubation Results are recorded and the records maintained. Positive process control Negative process control
С	2,5		2.5.10	Inoculated tubes are placed in an air incubator at $35 \pm 0.5^{\circ}$ C for $3 \pm 0.5$ hours of resuscitation.
С	5		2.5.11	After $3 \pm 0.5$ hours resuscitation at 35°C, inoculated tubes are incubated at $44.5 \pm 0.2$ °C in a circulating waterbath for the remainder of the $24 \pm 2$ hours.
С	5		2.5.12	The presence of turbidity and any amount of gas or effervescence in the culture tube constitutes a positive test.
		2.6 Co		ion of Results – APHA MPN
K	9		2.6.1	Results of multiple dilution tests are read from tables in <i>Recommended</i> <i>Procedures for the Examination of Sea Water and Shellfish</i> , 4 <sup>th</sup> Edition.
K	7		2.6.2	Results from single dilution series are calculated from Hoskins' equation or interpolated from Figure 1, Public Health Report 1621 entitled "Most Probable Numbers for Evaluation of Coli aerogenes Tests by Fermentation Tube Method".
С	7,9		2.6.3	Results are reported as MPN/100 mL of sample.
			TEC A	ogical Analysis of Seawater by Membrane Filtration (MF) using gar - Materials and Equipment
C	23, 24		2.7.1	When used for elevated temperature incubation in conjunction with ethafoam resuscitation, the temperature of the hot air incubator is maintained at $44.5 \pm 0.5^{\circ}$ C under any loading capacity.
С	23		2.7.2	When using a waterbath for elevated temperature incubation, the level of the water completely covers the plates.
С	23		2.7.3	Pre-sterilized plastic or sterile glass culture plates that are clear, flat bottomed, free of bubbles and scratches with tight fitting lids are used.
С	2		2.7.4	The sterility of pre-sterilized culture plates is determined for each lot received. Results are recorded and the records maintained.
K	11		2.7.5	Colonies are counted with the aid of magnification.
С	11, 23		2.7.6	Membrane filters are made from cellulose ester material, white, grid marked, 47 mm in diameter with a pore size of 0.45 µm and certified by the manufacturer for fecal coliform analyses.
С	2		2.7.7	Lot number, date of receipt and if provided the expiration date of the membrane filters are recorded and records maintained.
С	2		2.7.8	When initiating monitoring by mTEC or switching brands or types of membrane filters used and no previous lots of filters are available for comparing acceptable performance, an appropriate method for determining the suitability of the lot is developed and the comparison testing implemented. The results are recorded and this record is maintained.
K	2, 11		2.7.9	New lots of membrane filters are checked by comparing recovery of fecal coliform organisms against membrane filters from previously acceptable lots.
С	2		2.7.10	The sterility of each lot or autoclave batch of membrane filters are checked before use.
K	2		2.7.11	Membrane filters which are beyond their expiration date are not used.
0	11		2.7.12	Forceps tips are clean.

			110p03d117-133
11		2.7.13	Forceps tips are smooth without pitting or corrugations to damage the filters being manipulated.
11		2.7.14	Forceps are dipped in alcohol and flame sterilized between sample filters.
11		2.7.15	If indelible graduation marks are used on clear glass or plastic funnels to measure sample volumes, their accuracy is checked gravimetrically or with a Class A graduated cylinder before use and periodically rechecked. Funnels having a tolerance greater than 2.5% are not used. Checks are recorded and records maintained.
11		2.7.16	Membrane filtration units are made of stainless steel, glass or autoclavable plastic free of scratches, corrosion and leaks.
11		2.7.17	Membrane filter assemblies are autoclave sterilized for 15 minutes at 121°C prior to the start of a filtration series.
11, 23, 26		2.7.18	A UV sterilization unit is used to disinfect filter assemblies between sample and filtration runs.
11		2.7.19	The effectiveness of the UV sterilization unit is determined by biological testing monthly. Results are recorded and records maintained.
2		2.7.20	Maintenance of the UV sterilization unit is performed as needed. This maintenance is documented and the records maintained.
	2.8 M	edia Pre	paration and Storage – MF using mTEC Agar
11		2.8.1	Phosphate buffered saline is used as the sample diluent and filter funnel rinse.
11		2.8.2	The phosphate buffered saline is properly sterilized.
23		2.8.3	A sufficient amount of medium (4-5 mL) is used in each plate.
11		2.8.4	Refrigerated prepared plates are stored for no more than 2 weeks in sealed plastic bags or containers to minimize evaporation.
	2.9 Sa	mple Ar	alyses - MF using mTEC Agar
24		2.9.1	mTEC agar is used.
2		2.9.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained.Positive productivity controlNegative productivity control
23		2.9.3	The sample is shaken vigorously (25 times in a 12" arc in 7 seconds) before filtration.
23		2.9.4	The membrane is placed grid side up within the sterile filter apparatus.
23, 25		2.9.5	Sample volumes tested are consistent with the sampling regime employed (i.e., half log or other appropriate dilutions are used with systematic random sampling).
23		2.9.6	Sample volumes are filtered under vacuum.
26		2.9.7	The pressure of the vacuum pump does not exceed 15 psi.
23, 26		2.9.8	The sides of the filter funnel are rinsed at least twice with 20-30 mL of sterile phosphate buffered saline after sample filtration.
23		2.9.9	The membrane filter is removed from the filtering apparatus with sterile forceps and rolled onto mTEC agar so that no bubbles form between the filter and the agar.
11		2.9.10	Blanks are run at the beginning of filtration, after every 10 <sup>th</sup> aliquot and at the end of the filtration run to check the sterility of the testing system (phosphate buffered saline, filter funnel, forceps, membrane filter, media and culture plate).
2, 11		2.9.11	Appropriately diluted process control cultures accompany the samples throughout both resuscitation and elevated temperature incubation. Results are recorded and the records maintained.
			Positive process control Negative process control
11, 23, 24		2.9.12	Inoculated plates are placed inverted into a watertight, tightly sealed
	11         11         11         11         11         11         11, 23, 26         11         2         11         23         23         23         23         23         23         23         23         23         23         23         23         23         23         23         23         21         11	11       11         11       11         11       11         11       11         11       11         11       11         2       11         11       11         23       11         23       11         23       11         23       11         23       12         23       12         23       12         23       12         23       12         23       12         23       12         23       13         23       14         11       15         11       16         11       17         11       18         11       19         11       10         11       11         11       11	11       2.7.14         11       2.7.15         11       2.7.15         11       2.7.16         11       2.7.16         11       2.7.17         11, 23, 26       2.7.18         11       2.7.19         2       2.7.19         2       2.7.19         2       2.7.20         2.8 Media Pre         11       2.8.1         11       2.8.2         23       2.8.3         11       2.8.4         2.9 Sample Ar         24       2.9.1         2       2.9.2         23       2.9.4         23, 25       2.9.5         23       2.9.7         23, 26       2.9.7         23, 26       2.9.7         23, 26       2.9.8         23       2.9.9         11       2.9.9

				Pioposai 19-155
				0.5°C for 2 hours of resuscitation. Alternatively inoculated plates may be placed in ethafoam prior to air incubation at $44.5 \pm 0.5$ °C for $24 \pm 2$ hours.
С	11, 23, 24		2.9.13	After 2 hours of resuscitation at 35°C, the watertight, tightly sealed
-	, -,			containers are transferred to a circulating waterbath at 44.5 + 0.2°C,
				submerged completely and incubated for 22-24 hours.
				2.10 Computation of Results - MF using mTEC Agar
С	23		2.10.1	All yellow, yellow-green or yellow-brown colonies are counted.
С	23		2.10.2	Only plates having 80 or fewer colonies are counted. If it is unavoidable to use plates having more than 80 colonies, counts are given as >80 x 100/the volume of sample filtered.
С	2, 11, 23		2.10.3	When multiple dilutions are filtered, the laboratory has developed a procedure for assessing the contribution of all positive dilutions to the final count.
С	23, 11		2.10.4	The number of fecal coliforms is calculated by the following equation:
				Number of fecal coliforms per 100 mL = [number of colonies counted per plate used in the count / volume (s) of sample filtered in ml] x 100.
С	23, 11		2.10.5	Results are reported as CFU/100 mL of sample.
			Р	ART III - SHELLFISH SAMPLES
		3.1 Co	llection	and Transportation of Samples
С	9		3.1.1	A representative sample of shellstock is collected.
K	9		3.1.2	Shellstock samples are collected in clean, waterproof, puncture resistant containers loosely sealed.
K	9		3.1.3	Shellstock samples are labeled with collector's name, type of shellstock, the source or harvest area, sampling station, time, date and place (if applicable ) of collection.
С	9		3.1.4	Immediately after collection, shellfish samples are placed in dry storage (ice chest or equivalent) which is maintained between 0 and 10°C with ice or cold packs for transport to the laboratory. Once received, the samples are placed under refrigeration unless processed immediately.
С	1		3.1.5	Analysis of the samples is initiated as soon as possible after collection. Shellfish samples are not tested if the time interval between collection and analysis exceeds 24 hours.
		3.2 Pr	eparatio	on of Shellfish for Examination
K	2,11			
	2,11		321	
-			3.2.1	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use.
0	2		3.2.1 3.2.2	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15
0	2 9			Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use.
			3.2.2	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water
0	9		3.2.2       3.2.3	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris.
0 0	9 2		3.2.2       3.2.3       3.2.4	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris. The faucet used for rinsing the shellstock does not contain an aerator. Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of
O O K	9 2 9		3.2.2         3.2.3         3.2.4         3.2.5	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris. The faucet used for rinsing the shellstock does not contain an aerator. Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of drinking water quality. Shellstock are allowed to drain in a clean container or on clean towels prior to
0 0 K 0	9 2 9 9 9		3.2.2         3.2.3         3.2.4         3.2.5         3.2.6	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris. The faucet used for rinsing the shellstock does not contain an aerator. Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of drinking water quality. Shellstock are allowed to drain in a clean container or on clean towels prior to opening. Immediately prior to shucking, the hands (or gloved hands) of the analyst are
0 0 K 0 K	9 2 9 9 9 9		3.2.2         3.2.3         3.2.4         3.2.5         3.2.6         3.2.7	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris. The faucet used for rinsing the shellstock does not contain an aerator. Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of drinking water quality. Shellstock are allowed to drain in a clean container or on clean towels prior to opening. Immediately prior to shucking, the hands (or gloved hands) of the analyst are thoroughly washed with soap and water and rinsed in 70% alcohol.
0 K 0 K C	9 2 9 9 9 9 9 9 9		3.2.2         3.2.3         3.2.4         3.2.5         3.2.6         3.2.7 <b>3.2.8</b>	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use. Blades of shucking knives are not corroded. The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris. The faucet used for rinsing the shellstock does not contain an aerator. Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of drinking water quality. Shellstock are allowed to drain in a clean container or on clean towels prior to opening. Immediately prior to shucking, the hands (or gloved hands) of the analyst are thoroughly washed with soap and water and rinsed in 70% alcohol. Shellstock are not shucked directly through the hinge. Contents of shellstock (liquor and meat) are shucked into a sterile, tared
O K O K C C	9 2 9 9 9 9 9 9 9 9 9 9		3.2.2         3.2.3         3.2.4         3.2.5         3.2.6         3.2.7 <b>3.2.8 3.2.9</b>	<ul> <li>Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15 minutes prior to use.</li> <li>Blades of shucking knives are not corroded.</li> <li>The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris.</li> <li>The faucet used for rinsing the shellstock does not contain an aerator.</li> <li>Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of drinking water quality.</li> <li>Shellstock are allowed to drain in a clean container or on clean towels prior to opening.</li> <li>Immediately prior to shucking, the hands (or gloved hands) of the analyst are thoroughly washed with soap and water and rinsed in 70% alcohol.</li> <li>Shellstock are not shucked directly through the hinge.</li> <li>Contents of shellstock (liquor and meat) are shucked into a sterile, tared blender jar or other sterile container.</li> </ul>

				diluent is added.
0	9		3.2.13	Sterile phosphate buffered dilution water is used as the sample diluent.
С	9		3.2.14	Samples are blended at high speed for 60 to 120 seconds until homogenous.
K	9		3.2.15	APHA <i>Recommended Procedures for the Examination of Sea Water And</i> <i>Shellfish</i> , Fourth Edition is followed for the analysis of previously shucked and frozen shellfish meats.
		3.3 MI	- PN Anal	ysis for Fecal Coliform Organisms, Presumptive Test, APHA
С	9		3.3.1	Appropriate strength lactose or lauryl tryptose broth is used as
				presumptive media in the analysis. (Circle the medium used.)
С	2		3.3.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained. Positive productivity controlNegative productivity control
K	9		3.3.3	Immediately (within 2 minutes) after blending, the ground sample is diluted and inoculated into tubes of presumptive media.
С	9		3.3.4	No fewer than 5 tubes per dilution are used in a multiple dilution MPN series.
С	9		3.3.5	Allowing for the initial 1:1 dilution of the sample, appropriate portions are inoculated (i.e., 2 ml of original 1:1 dilution for the 1 g portion) and diluted for subsequent inoculation (i.e., 20 ml of 1:1 diluted sample to 80 ml of diluent or the equivalent for 0.1 g portion). All successive dilutions are prepared conventionally.
K	6		3.3.6	In a single dilution series, the volumes examined are adequate to meet the needs of routine monitoring. Sample volume inoculatedRange of MPNStrength of media used
С	2		3.3.7	Appropriately diluted process control cultures accompany the samples throughout both the presumptive and confirmed phases of incubation. Results are recorded and the records maintained. Positive Process control Negative Process control
K	9		3.3.8	Inoculated media are incubated at $35 \pm 0.5^{\circ}$ C.
K	10		3.3.9	Tubes are read after $24 \pm 2$ hours of incubation and transferred if positive for growth (the presence of turbidity and gas or effervescence in the culture tube). These tubes are considered presumptive requiring further confirmatory testing.
		3.4 Co	nfirmed	Test for Fecal Coliforms - APHA
С	9		3.4.1	EC medium is used as the confirmatory medium.
С	2		3.4.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained. Positive productivity control Negative productivity control
K	9, 11		3.4.3	Transfers are made to EC medium by either sterile loop or hardwood sterile transfer sticks from positive presumptives. ( <i>Circle the method of transfer.</i> )
С	9		3.4.4	EC tubes are incubated in a circulating waterbath at $44.5 \pm 0.2^{\circ}C$
K	9	╞╋	3.4.5	EC tubes are read for gas production after $24 \pm 2$ hours of incubation.
C	9	Ť	3.4.6	The presence of turbidity and any amount of gas and/or effervescence in the Durham tube constitutes a positive test.
<u> </u>	<u> </u>	3.5 Co	 mputati	ion of Results for MPN Analyses
K	9		3.5.1	Results of multiple dilution tests are read from tables in <i>Recommended</i> <i>Procedure for the Examination of Sea Water and Shellfish,</i> 4th Edition and multiplied by the appropriate dilution factor.
K	7		3.5.2	Results from single dilution series are calculated from Hoskins' equation or interpolated from Figure 1, Public Health Report 1621 entitled "Most Probable Numbers for Evaluation of Coli aerogenes Tests by Fermentation Tube Method".
	Section 1	v cinda	ince Doci	ments – Chapter II. Growing Areas NSSP Lab Evaluation Checklist

С	9		3.5.3	Results are reported as MPN/100 grams of sample.
		3.6 Sta	ndard ]	Plate Count Method
0	20		3.6.1	A standard plate count (SPC) analysis may be performed in conjunction with the analysis for fecal coliform organisms.
K	9		3.6.2	In the standard plate count procedure at least four plates are used, duplicates of two dilutions. One of the dilutions should produce colonies of 30 to 300 per plate.
K	2		3.6.3	Fifteen to 20 mL of tempered sterile plate count agar is used per plate.
С	9		3.6.4	Agar tempering bath maintains the agar at 44-46°C.
С	9		3.6.5	An agar based temperature control having a similar volume and shape as the tempering plate count agar is used in the tempering bath.
K	9		3.6.6	Samples or sample dilutions to be plated are shaken vigorously (25 times in a 12" arc in 7 seconds) before plating.
С	9		3.6.7	Not more than 1 mL nor less than 0.1 mL of sample or sample dilution is plated.
K	11		3.6.8	Control plates are used to check air quality and the sterility of the agar and the diluent.
K	9,21		3.6.9	Solidified plates are incubated at $35 \pm 0.5$ °C for $48 \pm 3$ hours inverted and stacked no more than four high.
K	9		3.6.10	Quebec Colony Counter or its equivalent is used to provide the necessary magnification and visibility for counting plates.
K	1		3.6.11	A hand tally or its equivalent is used for accuracy in counting.
		3.7 Co		ion of Results -SPC
K	9		3.7.1	Colony counts determined in accordance with Part III, A, Sections 4.31 through 4.33 in <i>Recommended Procedures for the Examination of Sea Water and Shellfish</i> , Fourth Edition.
С	19		3.7.2	Colony counts are reported as CFU/g of sample.
		3.8 Ba	cteriolo	gical Analysis of Shellfish Using the ETCP
С	2,3		3.8.1	Prepared modified MacConkey agar is used on the day that it is made.
K	3		3.8.2	Double strength modified MacConkey agar is used.
С	3		3.8.3	Prepared double strength modified MacConkey agar is heated to boiling, removed from the heat, and boiled again. This agar is never autoclaved.
K	2, 3		3.8.4	Twice boiled, double strength modified MacConkey agar and is maintained in a tempering bath at 45 to 50°C until used.
K	2, 3		3.8.5	Phosphate buffered saline is used as the sample diluent in the ETCP.
С	2, 3		3.8.6	The phosphate buffered saline is tempered at 45 - 50°C to prevent premature solidification of the agar.
С	9		3.8.7	The sample homogenate is cultured within 2 minutes of blending.
C	2,3		3.8.8	Six grams of shellfish (12 grams of homogenate if initially diluted 1:1) is placed into a sterile container and the contents brought up to 60 mL with sterile, tempered phosphate buffered saline.
K	3		3.8.9	Sixty (60) mL of tempered, twice boiled double strength Modified MacConkey Agar is added.
K	2,3, 22		3.8.10	The container is gently swirled or slowly inverted once to mix the contents, which are subsequently distributed uniformly over six plates.
С	1		3.8.11	Media and diluent sterility are determined with each use. Results are recorded and the records maintained.
С	1		3.8.12	Media productivity is determined using media appropriate properly diluted pour plated positive and negative control cultures for each batch of Modified MacConkey agar prepared.         Positive control culture Negative control culture
С	3, 13		3.8.13	When solidified, the plates are placed inverted into an air incubator at $45.5 \pm 0.5^{\circ}$ C for 18 to 30 hours of incubation.

~	•		0.0.1.1		
С	2			Plates are stacked no more than three high in the incubator.	
C	2		3.8.15	Appropriately diluted pour plated process control cultures accompany each set of samples throughout incubation. The results are recorded and the records maintained. Positive process control Negative process control	
	3.9 Computation of Results - ETCP				
K	11		3.9.1	Quebec Colony counter or its equivalent is used to provide the necessary magnification and visibility for counting.	
0	1		3.9.2	A hand tally or its equivalent is used to aid in counting.	
С	3,6		3.9.3	All brick red colonies greater than 0.5 mm in diameter are totaled over all	
			• • •	the plates and multiplied by a factor of 16.7.	
С	3		3.9.4	Results are reported as CFU/100 grams of sample.	
	Bacteriological Examination of Soft-shelled Clams and American Oysters for Male				
	Specific Coliphage (MSC)				
		3.10 M		ipment and Supplies	
K	30		3.10.1	Sample containers used for the shucked sample are sterile, made of glass or some other inert material (i.e. polypropylene) and hold $100 - 125$ mL.	
C	27, 28		3.10.2	The refrigerated centrifuge used must have the capacity to accommodate	
				the amount of shellfish sample required for the procedure, perform at 9000 x g and maintain a temperature of 4°C.	
K	9		3.10.3	The level of water in the tempering bath covers the level of liquid and agar in the	
				container or culture tubes.	
С	27, 28		3.10.4	Sterile 0.22 μm pore size syringe filters and pre-sterilized plastic or sterile glass syringes are used to sterilize the antibiotic solutions.	
K	1		3.10.5	The sterility of each lot of pre-sterilized syringes and syringe filters is determined. Results are recorded and records maintained.	
K	1		3.10.6	The sterility of each batch of reusable glass syringes is determined. Results are	
				recorded and records maintained.	
С	27, 28		3.10.7	The balance used provides a sensitivity of at least mg (0.01g.).	
С	27, 28		3.10.8	The temperature of the incubator used is maintained at $36 \pm 1^{\circ}$ C.	
C	28		3.10.9	Sterile disposable 50 mL centrifuge tubes are used and their sterility is determined with each lot. Results are recorded and records maintained.	
		3.11 M	ISC Me	dia Preparation	
K	28		3.11.1	Media preparation and sterilization is according to the validated method.	
K	27, 28		3.11.2	Bottom agar, double strength soft agar and growth broth are prepared from their	
	07.00		2 1 1 2	individual components.	
K	27, 28	⊢⊢	3.11.3	Soft agar is prepared double strength in volumes of 2.5 mL.	
C	27, 28		3.11.4	The streptomycin and ampicillin solutions are added to tempered bottom agar and vortex for 2 minutes on stir plate.	
0	27, 28		3.11.5	Storage of the bottom agar under refrigeration does not exceed 1 month.	
K	27, 28	┼╞╉╴	3.11.6	Unsterilized soft agar is stored at -20 °C -15C for up to 3 months.	
K	27, 28	┼┢╉	3.11.7	The soft agar is removed from the freezer and sterilized for 15 minutes at 121°C	
			2 11 0	before use.	
K	27, 28 3.11.8		5.11.8	Storage of growth broth in the refrigerator in loosely capped tubes/bottles does not exceed 1 month and in screw capped tubes/bottles does not exceed 3	
				months.	
K	27, 28		3.11.9	Bottom agar plates are allowed to reach room temperature before use.	
		3.12 P	reparati	on of the Soft-Shelled Clams and American Oysters for MSC Analysis	
K	2,11		3.12.1	Shucking knives, scrub brushes and blender jars are autoclave sterilized for 15 minutes prior to use.	
0	2		3.12.2	The blades of shucking knives are not corroded.	
0	9		3.12.3	The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris.	
	Section	IV Guida	nce Doci	ments – Chapter II. Growing Areas NSSP Lab Evaluation Checklist	

				1100000119 100
0	2		3.12.4	The faucet used for rinsing the shellfish does not contain an aerator.
K	9		3.12.5	The shellfish are scrubbed with a stiff, sterile brush and rinsed under tap water
				of drinking water quality.
0	9		3.12.6	The shellfish are allowed to drain in a clean container or on clean towels unlayered prior to shucking.
K	9		3.12.7	Immediately prior to shucking, the hands (or gloved hands) of the analyst are thoroughly washed with soap and water and rinsed in 70% alcohol.
С	9		3.12.8	Shellfish are not shucked through the hinge.
С	9		3.12.9	The contents of shellfish (liquor and meat) are shucked into a sterile, tared
				blender jar or other sterile container.
K	9			A representative sample of at least 12 shellfish is used for the analysis.
K	2, 19		1	The sample is weighed to the nearest 0.1 gram.
		3.13 N		mple Analysis
С	28		3.13.1	E.coli <i>Famp</i> ATCC 700891 is the bacterial host strain used in this procedure.
K	27, 28		3.13.2	Host cell growth broth is tempered at $36 \pm 1^{\circ}$ C and vortexed (or shaken) to aerate prior to inoculation with host cells.
K	27, 28		3.13.3	Several host cell colonies are transferred to a tube of tempered, aerated growth broth and incubated at $36 \pm 1^{\circ}$ C for 4-6 hours to provide host cells in log phase growth for sample analysis.
С	27, 28		3.13.4	After inoculation, the host cell growth broth culture is not shaken.
С	28		3.13.5	A 2:1 mixture of sterile growth broth to shellfish tissue is used for eluting the MSC.
С	28		3.13.6	The elution mixture is prepared w/v by weighing the sample and adding two equal portions of sterile growth broth by volume to the shellfish tissue.
С	28		3.13.7	The elution mixture is homogenized at high speed for 180 seconds.
С	28		3.13.8	Immediately after blending, 33 grams of the homogenized elution mixture are weighed into centrifuge tubes.
С	28		3.13.9	The homogenized elution mixture is centrifuged for 15 minutes at 9000 x g at 4°C.
С	27, 28		3.13.10	The supernatant is pipetted off, weighed and the weight recorded.
С	27, 28		3.13.11	The supernatant is allowed to warm to room temperature about 20 to 30 minutes.
K	27, 28		3.13.12	The autoclaved soft agar is tempered and held at $51 \pm 1^{\circ}$ C throughout the period of sample analysis.
K	27, 28		3.13.13	Two hundred microliters (0.2 mL) of log phase host strain <i>E coli</i> is added to the tempering soft agar immediately prior to adding the sample supernatant.
K	27, 28		3.13.14	The sample supernatant is shaken or vortexed before being added to the tempering soft agar.
С	27, 28		3.13.15	2.5 mL of sample supernatant is added to each tube of tempering soft agar.
С	27, 28			The soft agar/sample supernatant/host cell mixture is gently rolled between the palms of the hands to mix.
С	27, 28		3.13.17	The soft agar/sample supernatant/host cell mixture is overlaid onto bottom agar plates and swirled gently to distribute the mixture evenly over the plate.
С	28		3.13.18	Ten (10) plates are used, 2.5 mL per plate for a total of 25 mL of supernatant analyzed per sample.
K	27, 28			Negative and positive control plates are prepared and accompany each set of samples analyzed. The results are recorded and records maintained. Positive control
K	27, 28			Growth broth is used as the negative control or blank.
K	27, 28		3.13.21	Type strain MS2 (ATCC 15597) male specific bacteriophage appropriately diluted to provide countable low levels of phage is used as the positive control.

K       2       3.13.22       A negative control plate is plated at the beginning and end of each set of samples analyzed.         K       27, 28       3.13.23       The positive control is plated after all the samples are inoculated and immediately prior to the final negative control.         C       27, 28       3.13.24       All plates are incubated at 36 ± 1°C for 18 ± 2 hours.         3.14       Computation of Results - MSC         C       27       3.14.1       Circular zones of clearing or plaques of any diameter in the lawn of host bacteria are counted.         C       28, 32       3.14.2       The working range of the method is 1 to 200 PFU per plate. When there are no plaques on all ten plates, the count is <6 PFU/100 grams for softshelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate on all plates, the count is given as > 20,000 PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.         O       9       3.14.4       The MSC count is rounded off conventionally to give a whole number.			1	
C       27, 28       3.13.24 All plates are incubated at 36 ± 1°C for 18 ± 2 hours.         3.14 Computation of Results - MSC         C       27       3.14.1 Circular zones of clearing or plaques of any diameter in the lawn of host bacteria are counted.         C       28, 32       3.14.2 The working range of the method is 1 to 200 PFU per plate. When there are no plaques on all ten plates, the count is <6 PFU/100 grams for soft-shelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate on all plates, the count is given as > 20,000 PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.	K	2		
3.14 Computation of Results - MSC         C       27       3.14.1       Circular zones of clearing or plaques of any diameter in the lawn of host bacteria are counted.         C       28, 32       3.14.2       The working range of the method is 1 to 200 PFU per plate. When there are no plaques on all ten plates, the count is <6 PFU/100 grams for soft-shelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate on all plates, the count is given as > 20,000 PFU/100 grams.         K       28       3.14.3       The formula used for determining the density of MSC in PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.	K	27, 28		
C       27       3.14.1       Circular zones of clearing or plaques of any diameter in the lawn of host bacteria are counted.         C       28, 32       3.14.1       Circular zones of clearing or plaques of any diameter in the lawn of host bacteria are counted.         C       28, 32       3.14.2       The working range of the method is 1 to 200 PFU per plate. When there are no plaques on all ten plates, the count is <6 PFU/100 grams for soft-shelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate on all plates, the count is given as > 20,000 PFU/100 grams.         K       28       3.14.3       The formula used for determining the density of MSC in PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.	С	27, 28	<b>3.13.24</b> All plates are incubated at 36 ± 1°C for 18 ± 2 hours.	
C       28, 32       3.14.2       The working range of the method is 1 to 200 PFU per plate. When there are no plaques on all ten plates, the count is <6 PFU/100 grams for soft-shelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate on all plates, the count is given as > 20,000 PFU/100 grams.         K       28       3.14.3       The formula used for determining the density of MSC in PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.		3.14 Computation of Results - MSC		
K       28       3.14.3       The formula used for determining the density of MSC in PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.	С	27		
(0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.	С	28, 32	are no plaques on all ten plates, the count is <6 PFU/100 grams for soft- shelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate	
O 9 3.14.4 The MSC count is rounded off conventionally to give a whole number.	K	28	(0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates	
	0	9	3.14.4 The MSC count is rounded off conventionally to give a whole number.	

## REFERENCES

- 1. American Public Health Association 1984. *Compendium of Methods for the Microbiological Examination of Foods*, 2<sup>nd</sup> Edition. APHA, Washington, D.C.
- 2. Good Laboratory Practice.
- 3. "Interim Guides for the Depuration of the Northern Quahog, *Mercenaria mercenaria*." 1968. Northeast Marine Health Sciences Laboratory, North Kingstown, RI.
- 4. U.S. Department of Commerce. 1976. NBS *Monograph 150*. U.S. Department of Commerce, Washington, D.C.
- 5. Association of Official Analytical Chemists (AOAC). Current Edition. *Official Methods of Analyses of the Association of Official Analytical Chemists*. Official method 978.23. Chapter 17.305. AOAC Arlington, VA.
- 6. Wilt, D.S. (ed.). 1974. *Proceedings of the* δ<sup>th</sup> *National Shellfish Sanitation Workshop*. U.S. Food and Drug Administration, Washington, D.C.
- 7. U.S. Public Health Service (PHS). 1947. Public Health Report, Reprint #1621. PHS, Washington, D.C.
- 8. Association of Official Analytical Chemists (AOAC). 1991. *Quality Assurance Principles for Analytical Laboratories*. AOAC, Arlington, VA.
- 9. American Public Health Association (APHA). 1970. *Recommended Procedures for the Examination of Sea Water and Shellfish*, 4<sup>th</sup> Edition. APHA, Washington, D.C.
- 10. Interstate Shellfish Sanitation Conference (ISSC). 1986. *Shellfish Sanitation Interpretation #SS-39*. ISSC, Columbia, S.C.
- 11. American Public Health Association (APHA). 1992. *Standard Methods for the Examination of Water and Wastewater*, 18th Edition. APHA/AWWA/WEF, Washington, D.C.
- 12. Title 21, Code of Federal Regulations, Part 58, *Good Laboratory Practice for Nonclinical Laboratory Study*. U.S. Government Printing, Washington, D.C.
- 13. American Public Health Association (APHA). 1992. *Standard Methods for the Examination of Dairy Products*, 16<sup>th</sup> Edition. APHA, Washington, D.C.
- 14. Fisher, J. 1985. Measurement of pH. American Laboratory 16:54-60.
- 15. Consult pH electrode product literature.
- 16. Association of Official Analytical Chemists (AOAC). 1999. AOAC Methods Validation and Technical Programs Criteria for Laboratories Performing Food Testing. AOAC, Arlington, VA.
- 17. U.S. Environmental Protection Agency (EPA). 1975. *Handbook for Evaluating Water Bacteriological Laboratories*. EPA-670/9-75-006. U.S. EPA, Cincinnati, OH
- 18. Adams, W.N. 1974. NETSU. Personal communication to Dr. Wallace Andrews, FDA.
- 19. U.S. Food and Drug Administration (FDA).1995.*Bacteriological Analytical Manual*. U.S. FDA, 8<sup>th</sup> Edition, AOAC, Arlington, VA.
- 20. U.S. Food and Drug Administration (FDA) and Interstate Shellfish Sanitation Conference (ISSC). 1997. *NSSP Guide to the Control of Molluscan Shellfish*. FDA/ISSC, Washington, D.C. and Columbia, S.C.
- 21. U.S. Environmental Protection Agency. 1978. *Microbiological Methods for Monitoring the Environment, Water and Wastes*. EPA/600/8/78/017. EPA, Washington, D.C.

- 22. Furfari, Santo. March 21, 1972. Personal Communication to Dan Hunt, FDA.
- 23. United States Environmental Protection Agency, *Improved Enumeration Methods for the Recreational Water Quality Indicators: Enterococci and Escherichia coli*. EPA/821/R-97-004, EPA, Washington, DC
- 24. Rippey, Scott, R, Adams, Willard, N, and Watkins, William, D. Enumeration of fecal coliforms and *E. coli* in marine and estuarine waters: an alternative to the APHA-MPN approach, Journal WPCF, 59, 8 (1987).
- 25. FDA Manual of Interpretations, National Shellfish Sanitation Program *Guide for the Control of Molluscan Shellfish*, 2003 Revision, Interpretation Number 03-IV-@.02-102.
- 26. *Membrane filtration: A Users Guide and Reference Manual*, Thomas D. Brock, Science Tech Inc., Madison, WI, 1983.
- 27. Proceedings of the Male-specific Bacteriophage (MSC) Workshop, Gloucester, MA, March 9-12, 2004.
- 28. MSC Method and SLV write-up, Proposal 05-114 Spinney Creek Shellfish, Inc., September, 2009.
- 29. American Public Health Association. 1970. *Recommended Procedures for the Examination of Sea Water and Shellfish*, 4th Edition, APHA, New York, N.Y.
- 30. ASTM Manual on the Use of Thermocouples in Temperature Measurement, MNL-12 (ASTM, West Conshohocken, PA, 1993).
- 31. JOHN KAROLUS, MERCURIA CUMBO, SUSAN BOEHLER, and LAURA SAVINA. Modification of an Approved Medium for Fecal Coliform Detection in Seawater: A-1 Medium Minus Salicin. *Journal of Food Protection*: Vol. 66, No. 1, pp. 120–121.
- 32. MSC Method and SLV write-up, Proposal 13-120 Spinney Creek Shellfish, Inc., January, 2014.
- 33. American Public Health Association (APHA). 2017. *Standard Methods for the Examination of Water and Wastewater*, 23<sup>rd</sup> Edition, APHA/AWWA/WEF. Pg. 9-8 and 9-10.
- 34. Difco Manual, 11th Edition, 1998, Division of Becton Dickinson and Company, Sparks, Maryland, Pg. 13.

## SHELLFISH LABORATORY EVALUATION CHECKLIST

## SUMMARY OF NONCONFORMITIES

Page	Item	Observation	Documentation Required
		1	
		1	
		T	
		1	
		1	

LABORATORY STATUS							
LABORATORY	DATE						
LABORATORY REPRESENTATIVE:							
MICROBIOLOGICAL COMPONENT: (Part I-III)							
A. Results							
Total # of Critical (C) Nonconformities in Parts I-III							
Total # of Key (K) Nonconformities in Parts I-III							
Total # of Critical, Key and Other (O)							
Nonconformities in Parts I-III							
<b>B.</b> Criteria for Determining Laboratory Status of the Microbiolog	gical Component:						
1. <b>Does Not Conform Status</b> : The Microbiological component of this laboratory is not in conformity with NSSP requirements if:							
a. The total # of Critical nonconformities is $\geq$ 4 or							
b. The total # of Key nonconformities is $\geq$ 13 or							
c. The total # of Critical, Key and Other is $\geq 18$							
2. Provisionally Conforms Status: The microbiological component of this laboratory is determined to be provisionally conforming to NSSP requirements if the number of critical nonconformities is $\geq 1$ but $\leq 3$ .							
C. Laboratory Status (circle appropriate)							
Does Not Conform   Provisionally Conforms   O	Conforms						
Acknowledgment by Laboratory Director/Supervisor:							
All corrective Action will be implemented and verifying substantiating documentation received by the Laboratory Evaluation Officer on or before							
Laboratory Signature:	Date:						
LEO Signature:	Date:						

NSSP Form LAB-100 Microbiology Rev. October 2015